

# **PREPARE FOR CITY OF BROOKINGS,SD.**

**NEW Peterbilt Model 520 Refuse Chassis.**

**Selling price including predelivery and freight to packer factory**

**(PX-9 ENGINE, 3000 RDS TRANS, 40,000# REAR/SUSP)**

**This is a Sourcewell/NJPA contract# 060920      Oct 1,2021 Revision**

**Priced is based on second half of year build if truck slot is available.**

**Revised Spec's as of 10.12.21 - Sear C-2 Driver Seat,Haulmaxx Susp,2 additional years of Allison coverage totaling 5 years.**

## **NOTES:**

- (1) Price does not include any state or federal taxes.**
- (2) Price includes all standard warranties and Extended Engine/Aftertreatment coverage.**
- (3) Approximate delivery date for truck to body builder is Based on Availability.**
- (4) Payment due when complete unit is delivered to the City of Brookings.**
- (5) Peterbilt meets or exceeds all City of Brookings Specification.**

**BY  
LES DONDONEAU  
PETERBILT OF FARGO**



## Allstate Peterbilt of Fargo

3611 38th Street SW  
Fargo, ND 58104

701-282-6200 | 800-342-4949  
FAX: 701-281-0333

Oct. 20. 2021  
City of Brookings  
520 3<sup>rd</sup> St.  
Brookings SD 57006

We are pleased to offer the following for your consideration. In accordance with the Sourcewell/ NJPA Contract# 060920:

One (1) New model 520 Peterbilt :

20,000 lb. Front axle & Front suspension  
40,000 lb. Rear axle & Rear suspension  
Paccar PX-9 360 HP Diesel Engine  
Allison 3000 RDS-P Automatic Transmission

Basic One (1) year standard warranty  
See attached form.

Total Peterbilt List Price	\$211,888.00
35.00% NJPA/Sourcewell Contract discount	<u>(\$74,160.00)</u>
<b>Total NJPA/Sourcewell price for Peterbilt 520</b>	<b>\$137,728.00</b>

Sourced goods/Open-market items (not subject to NJPA contract):

Pre-delivery detail	\$625.00
Del/DEF/Fuel	\$1,189.00
Floor plan cost	\$3,231.00
Doc Fee	\$400.00
Training	\$500.00
Manuals	\$675.00
Engine/Aftertreatment 5yr-100,000 mile coverage	\$2,890.00
Extended 1 year towing Warranty	\$300.00
Allison 2 Add YR Totaling 5 YR	\$1,252.00
HD Sir Charge <b>AT THIS TIME</b>	<u>\$0.00</u>
Total for sourced goods/Open Market Items	\$11,062.00
+	
NJPA price for Peterbilt 520	\$137,728.00
<b>Total Delivered Price for Peterbilt Truck only</b>	<b>\$148,890.00</b>

SALES | PARTS | SERVICE | LEASING | RENTAL | FINANCE

ALEXANDRIA, MN | BISMARCK, ND | CLEVELAND, OH | DICKINSON, ND | EAU CLAIRE, WI | FARGO, ND | FINDLAY, OH | GRAND FORKS, ND | LA CROSSE, WI | MANKATO, MN | NEW PHILADELPHIA, OH  
RAPID CITY, SD | ROGERS, MN | SOUTH ST. PAUL, MN | SUPERIOR, WI | TOMAH, WI | WILLISTON, ND | WINONA, MN | WINONA DIESEL, MN | YOUNGSTOWN, OH [allstatepeterbilt.com](http://allstatepeterbilt.com)



## Allstate Peterbilt of Fargo

3611 38th Street SW  
Fargo, ND 58104

701-282-6200 | 800-342-4949  
FAX: 701-281-0333

Date of Acceptance

10-20-21

By:

*[Signature]*

Peterbilt of Fargo, Inc

Salesperson X

SALES | PARTS | SERVICE | LEASING | RENTAL | FINANCE

ALEXANDRIA, MN | BISMARCK, ND | CLEVELAND, OH | DICKINSON, ND | EAU CLAIRE, WI | FARGO, ND | FINDLAY, OH | GRAND FORKS, ND | LA CROSSE, WI | MANKATO, MN | NEW PHILADELPHIA, OH  
RAPID CITY, SD | ROGERS, MN | SOUTH ST. PAUL, MN | SUPERIOR, WI | TOMAH, WI | WILLISTON, ND | WINONA, MN | WINONA DIESEL, MN | YOUNGSTOWN, OH [allstatepeterbilt.com](http://allstatepeterbilt.com)



Peterbilt Of Fargo (P121)  
3611 38Th St. Sw  
Fargo, North Dakota 58104

City Of Brookings  
530 3Rd St  
Brookings, South Dakota 57006  
United States of America

Les Dondoneau  
Cell Phone: 701-282-6200  
Office Phone: 701-282-6200  
Email: ldondoneau@wdlarson.com

## Vehicle Summary

Model:	Unit	Model 520	Fr Axle Load (lbs):	20000
Type:		Full Truck	Rr Axle Load (lbs):	40000
Description 1:		Tandem 2023	G.C.W. (lbs):	60000
Description 2:				
Intended Serv.:	Application	Refuse/On-Highway	Road Conditions:	
Commodity:		Refuse, Scrap, Recycling	Class A (Highway)	95
			Class B (Hwy/Mtn)	5
			Class C (Off-Hwy)	0
			Class D (Off-Road)	0
Type:	Body	Curbside Recycler	Maximum Grade:	6
Length (ft):		20	Wheelbase (in):	196
Height (ft):		13.5	Overhang (in):	60
Max Laden Weight (lbs):		6000	Fr Axle to BOC (in):	0.1
			Cab to Axle (in):	195.9
			Cab to EOF (in):	255.9
			Overall Comb. Length (in):	313.6
No. of Trailer Axles:	Trailer	0		
Type:				
Length (ft):		0	Special Req.	
Height (ft):		0		
Kingpin Inset (in):		0		
Corner Radius (in):		0		
	Restrictions			
Length (ft):		40		
Width (in):		102		
Height (ft):		13.5		

Approved by: \_\_\_\_\_

Date: \_\_\_\_\_

Note: All sales are F.O.B. designated plant of manufacture.





Sales Code	Std/ Opt	Description	Weight
<b>Base Model</b>			
0005201	S	<b>Model 520</b> Peterbilt's Model 520 is built to withstand the harsh demands of the refuse industry. The rugged, aluminum cab delivers best-in-class durability for increased uptime and lap seam construction on a zinc-coated steel sub-frame for corrosion resistance. Bulkhead-style doors provide years of watertight performance. This low-cab forward vehicle adds a new dimension of productivity and versatility. An industry-leading, 65-degree cab tilt enhances maintenance and serviceability. Body installation is cost effective and efficient and the center console provides convenient access to body control integration points.	16,475
0091180	S	<b>Refuse, Scrap, Recycling</b>	0
0093035	S	<b>Refuse/On-Highway</b> Truck or tractor which hauls refuse, recycled material, etc. Includes roll-on/roll-off container movement, as well as hauling refuse from transfer stations to, but not into, landfills.	0
0095240	S	<b>Curbside Recycler</b> A lift-equipped truck used to load residential recycling bins into the truck body. Recycling material is removed by the body by hydraulic tilt.	0
0098170	S	<b>United States Registry</b> Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0
<b>Configuration</b>			
0200700	S	<b>Not Applicable</b> Secondary Manufacturer	0
<b>Frame &amp; Equipment</b>			
0514150	S	<b>10-3/4" Steel Rails To 305"</b> 10.75x3.5x.375 Dimension, 2,136,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair	112
0601500	O	<b>Full Steel Inner Liner</b>	631
0620110	O	<b>FEPTO Provision 9in Bumper Extension</b> Includes 1350 Series Front Drive PTO Attachment Provision, Radiator with PTO Cut-Out in Grille, Radiator Protection Sleeve, and Bumper Extension	42
0644020	O	<b>EOF Square with Steel Crossmember</b>	64
0651090	S	<b>Omit Rear Mudflaps and Hangers</b>	0
<b>Front Axle &amp; Equipment</b>			
1011890	S	<b>PACCAR FX-20 Steer Axle 20,000 lbs. 4" Drop</b> Axle is designed for applications with a gross axle weight rating (GAWR) of 20,000 pounds. Front axle is designed for demanding applications such as construction, heavy haul, refuse, and other	0

Price Level: April 1, 2021

100% Complete

Date: October 12, 2021

Deal: Tandem 2023

Quote Number: QUO-837253-T1S2R6

Printed On: 10/20/2021 5:37:21 AM



Sales Code	Std/ Opt	Description	Weight
		vocational uses. Robust forged steel beam construction for long-lasting performance. It utilizes innovative tapered kingpin roller bearings for more efficient operation and improved steering efficiency.	
		The PACCAR Steer Axle comes standard with the PACCAR warranty of 5 years, 750,000 miles.	
1114030	S	<b>Taper Leaf Springs, Shocks 20,000 lb</b> Standard with Heavy Resistance Shocks.	0
1243010	S	<b>Power Steering Sheppard M100 Dual</b> For use with 16,000 to 20,000 lb. axle ratings. Glidekote splines on steering shaft extend service life of components.	0
1354840	O	<b>PHP10 Iron PreSet PLUS Hubs</b> PHP10 iron PreSet PLUS hubs have a fully integrated spindle nut design, an optimized wheel spacer, magnetic fill plug on drive and trailer hubs for inspection of metal particles in lubricant, with a long life oil seal and bearings are pre-adjusted. Use with Front Axle.	84
1380280	O	<b>Bendix Air Cam Front Drum Brakes 16.5x7</b> For use with 16,000 lbs to 23,000 lbs steer axles or front drive axles. Includes automatic slack adjusters & outboard mounted brake drums.	0
1380490	O	<b>PACCAR FX Wide Track IPO Standard</b> 71in KPI IPO 69in front axle for improved turning radius.	0
1390540	O	<b>Dust Shields, Cam Brakes, Front Axle</b>	4
1391410	O	<b>Gusseted Cam Brackets, Steer Axle</b>	0
1392970	O	<b>Heavy Duty Cam Bushings, Steer Axle</b>	0
<b>Rear Axle &amp; Equipment</b>			
1526150	O	<b>Meritor MT40-14X 40,000 lb</b> Interaxle diff lock air rocker occupies space of one gauge. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	-347
1616300	O	<b>PHP10 Iron PreSet PLUS Hubs</b>	0
1660000	O	<b>Dust Shields For Cam Brakes, Drive Axle(s)</b>	4
1672630	O	<b>Differential Lock Both Axles</b> Air Rocker Switch Occupies the Space of One Gauge	60
1680440	O	<b>Refuse Service Brakes, Steer And Drive Axles</b> Designed for heavy-duty applications for refuse industry, providing long brake life, safety and performance.	0
1680450	O	<b>Rear Brake Camshaft Reinforcement</b> Rear brake camshaft reinforcement helps guard against wear and corrosion.	9

Price Level: April 1, 2021

100% Complete

Date: October 12, 2021

Deal: Tandem 2023

Quote Number: QUO-837253-T1S2R6

Printed On: 10/20/2021 5:37:21 AM





Sales Code	Std/ Opt	Description	Weight
1680460	O	<b>Heavy Wall, Drive Axle(s)</b>	88
1680500	S	<b>SBM Valve</b> Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	0
1680550	O	<b>Upsize Parking Brakes</b>	0
1680910	O	<b>Heavy Duty Brake Drums, Drive Axle(s)</b> Use with 16.5x7 Brakes	21
1682430	S	<b>Anti-Lock Braking System (ABS) 4S4M</b> ABS-6. Includes air braking system.	0
1684200	S	<b>Synthetic Axle Lubricant All Axles</b> Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0
1687010	O	<b>Bendix Air Cam Rear Drum Brakes 16.5x7</b> Bendix Air Cam Rear Drum Brakes to fit all heavy haul, construction, refuse and highway truck and tractor applications. Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums.	0
1706140	O	<b>Ratio 6.14 Rear Axle</b>	0
1824400	O	<b>Hendrickson HMX EX 400 40,000 Lbs., 54"</b> Haulmax, 60K Creep Rating. Includes Traax Rod as standard, option 1920905 is not needed or available. Progressive load spring system easily adjusts to the load for an enhanced combination of empty-ride quality and loaded stability.	-92

## Engine & Equipment

2074512	S	<b>PACCAR PX-9 360@2000 GOV@2200 1150@1200</b> Productivity (2021 Emissions)	0
		N21350 C121 64....Maximum Accelerator Pedal Ve	
		N21370 C128 64....Maximum Cruise Speed (P059)	
		N21460 C132 1400..Max PTO Speed (P046)	
		N21520 C133 5.....Timer Setting (P030)	
		N21610 C188 39....Low Ambient Temperature Thre	
		N21620 C189 60....Intermediate Ambient Tempera	
		N21630 C190 80....High Ambient Temperature Thr	
		N21550 C206 35....Engine Load Threshold (P516)	
		N21340 C209 120...Hard Maximum Speed Limit (P1	
		N21510 C225 YES...Enable Idle Shutdown Park Br	
		N21450 C231 NO....Gear Down Protection (P026)	
		N21570 C233 NO....Idle Shutdown Manual Overrul	

Price Level: April 1, 2021

100% Complete

Date: October 12, 2021

Deal: Tandem 2023

Quote Number: QUO-837253-T1S2R6

Printed On: 10/20/2021 5:37:21 AM



Sales Code	Std/ Opt	Description	Weight
		N21440 C234 NO....Engine Protection Shutdown (	
		N21480 C238 NO....Auto Engine Brake in Cruise	
		N21470 C239 NO....Cruise Control Auto Resume (	
		N21430 C333 0.....Reserve Speed Limit Offset (	
		N21410 C334 0.....Maximum Cycle Distance (N202	
		N21590 C382 YES...Enable Hot Ambient Automatic	
		N21500 C395 0.....Expiration Distance (N209)	
		N21530 C396 YES...Enable Impending Shutdown Wa	
		N21540 C397 60....Timer For Impending Shutdown	
		N21320 C399 120...Standard Maximum Speed Limit	
		N21400 C400 252...Reserve Speed Function Reset	
		N21420 C401 10....Maximum Active Distance (N20	
		N21330 C402 0.....Expiration Distance (N207)	
2091130	S	<b>VMUX Electronics Architecture</b>	0
2091305	O	<b>Engine Idle Shutdown Timer Enabled</b>	0
2091315	O	<b>Enable EIST Ambient Temp Override</b>	0
2091372		<b>Eff EIST NA Expiration Miles</b>	0
2091640		<b>Effective VSL Setting NA</b>	0
2092016	O	<b>Typical Operating Speed 62 MPH</b>	0
2092032	O	<b>Powertrain Optimized for Performance</b> Best analysis for vehicles used in vocational applications or with heavy GCWRs.	0
2140220	O	<b>CARB Engine Idling Compliance DECLINED By</b> Dealer/Customer	0
2140450	O	<b>Remote PTO/Throttle, 12-Pin</b> Eng Bay Remote Control Provision	0
2140670	O	<b>EPA Compliant Engine</b>	0
2147460	S	<b>Bed Plate for PX-9, L9N Engines</b> Designed to increase engine longevity by incorporating a stiffener bracket on the bottom side of the engine, inside the oil pan, for additional reinforcement. Required for all PX-9/L9N refuse applications and recommended for other high load 9-liter applications.	0
2513060	S	<b>PACCAR 160 Amp Alternator, Brushed</b> PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0
2521090	O	<b>Immersion Type Block Heater 110-120V</b> Standard location for 2.1M and 1.9M models is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	2
2522110	O	<b>PACCAR 12V Starter, N/A PACCAR MX Engines</b>	0

Price Level: April 1, 2021

100% Complete

Date: October 12, 2021

Deal: Tandem 2023

Quote Number: QUO-837253-T1S2R6

Printed On: 10/20/2021 5:37:21 AM





Sales Code	Std/ Opt	Description	Weight
		PACCAR 12-volt electrical system. With centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	
2538040	S	<b>3 PACCAR Premium 12V Dual Purpose Batt 2190 CCA</b> Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0
2539220	O	<b>Battery Jumper Terminals Mtd In Front</b> Of Battery Box	4
2539740	O	<b>Kissling Battery Disconnect Switch, 300 amp</b> Mounted on battery box	3
2621000	S	<b>2-Speed Fan Clutch For Frequent Start/Stops</b> A 2-speed fan clutch is ideal for vocational applications where the fan clutch engagement time exceeds 10% of the engine run time. When the fan clutch is disengaged, the fan still rotates at 15-25% of the engine RPM. This fan rotation provides crucial airflow to the engine and draws virtually no horsepower.	0
2723210	S	<b>18.7 CFM Air Compressor</b> N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	0
2921110	S	<b>PACCAR Fuel/Water Separator Standard Service</b> PACCAR Fuel/Water separator standard service intervals. High efficiency media protects critical engine components.	0
2921210	S	<b>No Fluid Heat Option for Fuel Filter</b>	0
2921310	S	<b>No Electric Heat Option for Fuel Filter</b>	0
3010400	O	<b>Engine Protection Shutdown w/ Label</b> Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature.	0
3114270	S	<b>High Efficiency Cooling System</b> Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 520: 1242 sq in.	0
3120450	S	<b>Stainless Steel Grille</b>	0
3261980	S	<b>Heavy Duty Air Cleaner</b> Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.	0
3365300	S	<b>Exhaust Vertical LH</b> DPF/SCR LH Back of Cab Vertical.	0
3381770	O	<b>Curved Tip Standpipe(s)</b>	1
3387870	S	<b>24" Ht, 5" Dia Chrome, Clear Coat Standpipe(s)</b>	0

Price Level: April 1, 2021

100% Complete

Date: October 12, 2021

Deal: Tandem 2023

Quote Number: QUO-837253-T1S2R6

Printed On: 10/20/2021 5:37:21 AM



Sales Code	Std/ Opt	Description	Weight
<b>Transmission &amp; Equipment</b>			
4052110	S	<b>Allison 3000 RDS-P Transmission, Gen 5</b> Rugged Duty Series. Includes Rear Transmission Support except on MX engines, Mobil Delvac Automatic Transmission Fluid, and Water-Oil Heat Exchange. Also includes features that monitor the transmission fluid, filter and clutch condition. Will display percent life remaining for the transmission fluid, filter and clutches on the shift selector. This information may be displayed using the Mode and Up and Down buttons. A wrench icon will also be included to indicate when the transmission fluid, filter or clutches need servicing. Suited for vehicles operating on/off highway and/or requiring PTO operation. Forward ratios: 1st-3.49, 2nd-1.86, 3rd-1.41, 4th-1.00, 5th-0.75, 6th-0.65. Reverse ratios: DR-(5.03).	0
4210080	O	<b>1710 HD Driveline, 1 Midship Bearing</b>	-20
4216590	O	<b>1710 Driveline Interaxle</b> For tandem rear axles	-5
4252170	O	<b>Auto Neutral Activates With Parking Brake</b> Auto Neutral helps improve jobsite safety by reducing the possibility of the truck moving due to throttle application.	0
4252840	S	<b>Allison FuelSense 2.0 Plus</b> Features include: EcoCal shift technology keeps the engine speed at the most efficient level, DynActive Shifting system incorporates a learning algorithm that selects variable shift points to find the ideal balance of fuel economy and performance, based upon the vehicle specifications and environmental parameters. This is valuable for applications with heavy start-stop needs like refuse, city delivery, and construction and Neutral at Stop reduces or eliminates the load on the engine when vehicle is stopped, lowering fuel consumption and emissions.	0
4252940	S	<b>Allison Neutral At Stop</b> Neutral at Stop features and benefits: Reduces or eliminates the load on the engine when vehicle is stopped, can help lower fuel consumption and CO2 emissions, and is included in FuelSense 2.0 Plus and Max packages only.	0
4256020	S	<b>Console Mounted Push Button Shifter</b> Allison Automatic Transmissions or LFNA Electric Vehicle	0
4256350	O	<b>Auto Neutral AK, Allison HD/RDS</b> Single steer left-hand or right-hand, add code 4540940 if plumbed to flip valve to actuate service brakes is desired	0
4256640	O	<b>Allison 6-Speed Configuration, Close Ratio Gears</b> 3000 Series Transmissions.	0
4256870	O	<b>Allison Output Function S Neutral Indicator</b> Allison output function S Neutral Indicator for PTO. Required on Refuse Packer Applications. With this configuration NEUTRAL only, PTO engagement is permitted only when the transmission is in Neutral. Once the transmission is in Neutral, the PTO is automatically engaged and fast idle is initiated when the PTO switch is on. In addition with this	0

Price Level: April 1, 2021

100% Complete

Date: October 12, 2021

Deal: Tandem 2023

Quote Number: QUO-837253-T1S2R6

Printed On: 10/20/2021 5:37:21 AM





Sales Code	Std/ Opt	Description	Weight
		configuration Pack-on-the-fly, the PTO is automatically engaged and fast idle is initiated when the PTO switch is On concurrently with shifting of the transmission to Neutral.	
<b>Air &amp; Trailer Equipment</b>			
4510210	S	<b>Bendix AD-HF EP Air Dryer, Heater</b> Coalescing filter, extended purge. Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technology in the the air dryer cartridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant.	-8
4520420	O	<b>Pull Cords All Air Tanks</b>	1
4540420	S	<b>Nylon Chassis Hose</b>	0
4543320	S	<b>Steel Painted Air Tanks</b> All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0
4543540	O	<b>Clear Outside Frame of All Air System Components</b> RH BOC	0
4612000	O	<b>Route AE Lines To Allow Welding Of Sub Frame</b> To top of frame 8" forward of back-of-cab to end-of-frame	0
<b>Tires &amp; Wheels</b>			
5064030	O	<b>FF: BR 20ply 425/65R22.5 M864</b> Efficiency Rating: Fair Diameter= 44.8 inches; SLR= 20.7 inches	58
5167310	O	<b>RR: BR 14ply 11R22.5 M843</b> Efficiency Rating: Poor Diameter= 42.5 inches; SLR= 19.9 inches	200
5190008	S	<b>Code-rear Tire Qty 08</b>	0
5220130	O	<b>FF: Alcoa 824627 22.5X12.25 High Polish</b> Aluminum	-74
5310600	S	<b>RR: Accur Stl Armor 50291PK 22.5X8.25</b> Heavy Duty, Two Hand Holes	0
5390008	S	<b>Code-rear Rim Qty 08</b>	0
<b>Fuel Tanks</b>			
5556130	O	<b>26" Aluminum 80 Gallon Fuel Tank LH BOC</b> Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup	13

Price Level: April 1, 2021

100% Complete

Date: October 12, 2021

Deal: Tandem 2023

Quote Number: QUO-837253-T1S2R6

Printed On: 10/20/2021 5:37:21 AM





Sales Code	Std/Opt	Description	Weight
		tube. Wire braid fuel lines increase durability & reduce potential for leaks.	
5604080	O	<b>Location LH BOC 80 Gallon</b>	0
5650490	S	<b>Fuel Cooler</b> Required with single fuel tank	0
5651390	O	<b>Top Of Fuel Tank 5" Below Top Of Frame</b>	33
5652890	S	<b>DEF Tank Mounted LH BOC</b> Models 220 and 520 mounted left hand back-of-cab.	0
5652980	S	<b>DEF To Fuel Ratio Between 1:1 And 2:1</b>	0
5655069	S	<b>DEF Tank 520, 7.3 Gal</b>	0
<b>Battery Box &amp; Bumper</b>			
6010460	O	<b>Aluminum Space Saver Battery Box LH Back Of Cab</b>	-11
6121700	S	<b>Steel Bumper Channel Painted</b> Includes two front tow eyes with pins	0
6132400	O	<b>Notched Top Flange Of Bumper</b> Does not include fepto provisions	0
<b>Cab &amp; Equipment</b>			
6501090	O	<b>53" LCF ProBilt Cab RH Drive</b> Use with auto-trans. Includes steel frames with aluminum and fiberglass panels, all aluminum doors, dual door stops, door locks, tinted safety glass thru-out, cab and door mounted entry grab handles, 65 degree hydraulic tilt, stainless steel grille, dual rear cab fenders, service module BOC (cab tilt pump, oil fill and dipstick, coolant fill and check, fluid fill and dipstick for auto trans), door mounted armrests, power windows, doghouse full insulation, rubber floor mats, ergonomic center control console, removable instrument panel, Driver Information Display, LED backlit gauges, adjustable side flip-down interior sunvisor, 16" steering wheel with integrated horn button, tilt/telescopic adjustable column, over-door storage, driver and passenger side cup holders, USB charging port and 12VDC charging outlet, header includes HVAC controls, rear cab corner windows, 18" bolt-on step on each side, self-canceling turn signals and Front Directional and Side Mounted Turn Signals.	0
6800500	S	<b>4.5" Rubber Flares On Cab</b> And wheel well fenders	0
6914160	O	<b>Sears C2 Plus Premium Driver Seat</b> Enhanced for operator comfort with a 1" thicker foam cushion with flat bolsters for greater surface area coverage. Countoured metal seat and back pans add to overall ergonomic design with air lumbar supprt. Comes with quick attach seat and back cushions for ease of service and replacement.	0
6921720	S	<b>Peterbilt Passenger Seat</b>	0

Price Level: April 1, 2021

100% Complete

Date: October 12, 2021

Deal: Tandem 2023

Quote Number: QUO-837253-T1S2R6

Printed On: 10/20/2021 5:37:21 AM



Sales Code	Std/Opt	Description	Weight
6939400	O	<b>Air Ride Driver</b>	43
6939430	O	<b>Mid Back Driver</b>	0
6939460	O	<b>Fabric Driver</b>	0
6939510	S	<b>Non-Air Ride Passenger</b>	0
6939540	S	<b>Low Back Passenger</b>	0
6939570	S	<b>Vinyl Passenger</b>	0
7000000	S	<b>Gray Interior Color</b> Includes ABS gray headliner & rear cab panel, gray vinyl engine tunnel cover. For LH, RH, and dual steer dual seated power windows are standard on both doors. For dual steer RH stand-up the LH window is power and the RH window is a manual sliding window.	0
7001520	S	<b>Adjustable Steering Column - Tilt/Telescope</b>	0
7001620	S	<b>Steering Wheel With Peterbilt Logo</b> Steering Wheel with embossed Peterbilt logo over horn button.	0
7110680	S	<b>Exterior Cab Entry Grabhandle</b> Textured; NFPA compliant. Available on Day Cab specifications only.	0
7220130	S	<b>Rear Window Back of Cab Standard Tint</b> 18.5in X 54in	0
7230350	S	<b>2-Piece Flat Windshield</b>	0
7322010	S	<b>Combo Fresh Air Heater/Air Conditioner</b> With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0
7564120	O	<b>Chromed LH/RH Dual Plane Mirrors, Heated,</b> Dual Plane motorized mirrors are mounted to doors on both the right and left hand sides. Available in chrome mirror shell with black arms. Includes fold-away feature and requires additional top mounted convex mirrors (7564160). For front loader body type configuration.	-5
7564160	O	<b>Add'l Convex Mirrors, Mounted Top of LH/RH</b> Dual Plane Mirrors	0
7610020	S	<b>(1) Air Horn 15" Painted</b> Mounted under cab.	0
7722120	O	<b>ConcertClass, AM/FM, Weatherband, 3.5 Aux</b>	10
7725740	O	<b>Midlevel Speaker Package For Cab</b> (4) Speakers	6
7728020	O	<b>Bluetooth Located On Driver Side</b>	0
7728030	O	<b>Radio Mute When In Reverse</b>	0

Price Level: April 1, 2021

100% Complete

Date: October 12, 2021

Deal: Tandem 2023

Quote Number: QUO-837253-T1S2R6

Printed On: 10/20/2021 5:37:21 AM





Sales Code	Std/ Opt	Description	Weight
		For automatic or automated transmission	
7728040	O	<b>Bluetooth Phone and Audio Requires USB Port</b>	0
7728050	O	<b>USB Port</b>	0
7788055	S	<b>SmartLINQ Remote Diagnostics</b> SmartLINQ is Peterbilts proprietary remote diagnostics service which monitors the engine and aftertreatment for diagnostic codes providing real-time code analysis maximizing vehicle uptime and strengthening the fleets partnership with their dealer. SmartLINQ provides fault coverage for over 800 codes, a customizable email notification for 116 codes plus a web portal to manage your entire fleet included at no additional charge. SmartLINQ is compatible with any telematics system and doesnt require a specific fleet management system. For those whose customers utilize PeopleNet, the pre-wire with remote diagnostics will provide a more integrated solution utilizing the existing SmartLINQ modem. For those whose customers utilize other fleet services products, the existing pre-wire option for the other fleet service devices will continue to be available. Standard on Class 8 engines and available on Models 348, 337, 330 and 325 with a PX-9, PX-7 or Cummins Westport natural gas engine.	0
7788057	O	<b>24 Months SmartLINQ Subscription</b> PACCAR PX Engines.	0
7851870	O	<b>Rain Gutters Over Driver and Passenger Doors</b>	8
7852150	S	<b>Peterbilt Pantograph Windshield Wipers</b> With intermittent feature.	0
7900090	O	<b>Triangle Reflector Kit, Ship Loose</b> Florescent triangle emergency road flares are designed to meet and exceed all DOT standards.	13
7900270	O	<b>Fire Extinguisher, Cab Mounted</b> Hazmat approved UL listed/rated ABC	12
7901130	O	<b>Backup Alarm (107 DB)</b>	3
8021315	S	<b>Air Restriction Indicator</b> Mounted on exhaust stanchion	0
8031120	O	<b>Warning Light Battery Disconnect, Switch Engaged</b> Marker light external mounted	0
8070860	O	<b>Main Instrumentation Panel</b> Digital Cluster 7" Display includes: Physical (Analog) - Speedometer, Tachometer, Oil Pressure, Coolant Temp and Display Gauges - Fuel Level, DEF Level, DPF Filter Status, Fuel Economy, Volts Telltale, OAT and Primary Air Pressure, Secondary Air Pressure for air brake trucks.	0
8110090	S	<b>Headlights Single Rectangular Halogen</b>	0
8120570	S	<b>(5) LED Clearance With (2) LED Marker Lights</b> Includes (5) lights mounted on roof of cab and (1) cab side marker light mounted in front of each cab door	0
8133900	S	<b>None Furnished Stop/Tail/Backup Lights</b>	0

Price Level: April 1, 2021

100% Complete

Date: October 12, 2021

Deal: Tandem 2023

Quote Number: QUO-837253-T1S2R6

Printed On: 10/20/2021 5:37:21 AM





Sales Code	Std/ Opt	Description	Weight
		Available with full truck only, not available with tractor	
8133960	O	<b>Daytime Running Lights</b> The brake interlock turns the daytime running lights off when the parking brakes are engaged. This is required on all Canadian vehicles.	0
8134160	O	<b>Self-Canceling Turn Signal</b>	0

#### Paint

8500710	S	<b>Standard Paint Color Selection</b>	0
8530770	O	<b>(1) Color Axalta Two Stage - Cab/Hood</b> Base Coat/Clear Coat N85020 A - L0006EY WHITE N85700 BUMPER L0001EA BLACK N85500 CAB ROOF L0006EY WHITE N85200 FRAME L0001EA BLACK	0

#### Shipping Destination

#### Options Not Subject To Discount

9400090	S	<b>Peterbilt Class 8 Standard Coverage</b> 1 year/100,000 Miles (160,000 km)	0
9400094	S	<b>PACCAR PX-9 Standard Coverage</b> 2 yrs/250,000 mi (402,336 km)/6,250 hrs	0
9402417	O	<b>1 Year Towing</b>	0
9407103	O	<b>Prepaid Freight Delivery Increase</b> For 2022 Delivery	0
9408703	O	<b>Base Warr: Emissions 5YR/100K MI-EPA Engine</b>	0

#### Miscellaneous

9409091	O	<b>State Registry: South Dakota</b>	0
9409897	O	<b>Cancel/Reorder Reorder Chassis</b>	0
9481975	O	<b>PACCAR 2021 PX-9 Protection Plan 1</b> 5 Yrs/100K Mi (160,935 Km)	0
9481987	O	<b>PACCAR 2021 PX-9 Aftertreatment Coverage (5/100)</b> 5 Yrs/100K Mi (160,935 Km)	0

#### Promotions

#### Order Comments

Price Level: April 1, 2021

100% Complete

Date: October 12, 2021

Deal: Tandem 2023

Quote Number: QUO-837253-T1S2R6

Printed On: 10/20/2021 5:37:21 AM



Total Weight

17,442

## Prices and Specifications Subject to Change Without Notice.

---

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in CRM.

---

### **PRICING DISCLAIMER**

*While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information*



**Shipping Destinations**

**Intermediate Destination:** none

Final Destinations	Quantity
--------------------	----------